



WORLD INTELLECTUAL PROPERTY
Organization



AB

INTERNATIONAL APPLICATION PUBLISHED UNDER

WO 9607371A1

(51) International Patent Classification 6:

A61F 2/06

A1

(11) International Publication Number:

WO 96/07371

(43) International Publication Date:

14 March 1996 (14.03.96)

(21) International Application Number: PCT/US95/11350

(22) International Filing Date: 5 September 1995 (05.09.95)

(30) Priority Data:
08/300,059 2 September 1994 (02.09.94) US

(71)(72) Applicant and Inventor: AHN, Sam, S. (US/US); Suite
510, 100 UCLA Medical Plaza, Los Angeles, CA 90024 (US).

(74) Agents: HOOVER, George, W. et al.; Blakely, Sokoloff,
Taylor & Zafman, 12400 Wilshire Boulevard, 7th floor, Los
Angeles, CA 90025-1026 (US).

(81) Designated States: AM, AT, AT (Utility model), AU, BB, BG,
BR, BY, CA, CH, CN, CZ, CZ (Utility model), DE, DE
(Utility model), DK, DK (Utility model), EE, EE (Utility
model), ES, FI, FI (Utility model), GB, GE, HU, IS, JP,
KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG,
MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE,
SG, SI, SK, SK (Utility model), TJ, TM, TT, UA, UG, UZ,
VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB,
GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ,
CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG),
ARIPO patent (KE, MW, SD, SZ, UG).


Published

With international search report.

(54) Title: APPARATUS AND METHOD FOR PERFORMING ANEURYSM REPAIR

(57) Abstract

The present invention is an apparatus and method of treating an aneurysm by applying to an aneurysmal blood vessel (22) a band (26) around its exterior surface, at the position where the attachment system (10a) of the graft (16) attaches the graft to the vessel. The band can be in the form of a strap with an attachment means such as hook and loop, clasp, sewn onto the vessel, or a heat sealing to the vessel.



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

APPARATUS AND METHOD FOR PERFORMING ANEURYSM REPAIR

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION

This invention relates to the field of vascular surgery, and more specifically, is directed to an apparatus and method for repairing a vascular aneurysm.

3. ART BACKGROUND

The prior art method of treating a vascular aneurysm and some other vascular problems has been to excise the aneurytic tissue and replace it with a synthetic graft or a graft from another section of the body. This surgery has been extremely risky, and a high mortality rate has been observed, primarily because the condition of the patients undergoing the surgery is generally weak.

In recent years, a number of companies have devised new methods and devices for treating aneurysms and other vascular disease in which the blood vessels are damaged and unable to safely retain the blood passing therethrough. The devices are comprised of vascular prosthetic graft with a connecting means of some type for connecting the prosthesis to the damaged blood vessel at a position displaced from the aneurysm or damage, the prosthesis being sized to fit within the blood vessel, so that the graft permits the blood to travel through the damaged vessel without applying any pressure to the damaged vessel at the point of damage.

U.S. Patent No. 4,140,126 discloses one such prior art device and method for repairing an aneurysm. This device is positioned in a vessel in a collapsed form, and is then expanded and then attached to the inside of the wall of the vessel with hooks which extend when the device is expanded from its collapsed form.

U.S. Patent No. 4,787,899 discloses an artificial intraluminal graft with u-shaped staples near the end for securing the graft to the vessel. U.S. Patent No. 5,104,399, which is a continuation in part of the '899 patent, discloses a generally cylindrical graft with a staple assembly in a v-shaped lattice work which is assembled into its operational configuration by the inflation of a balloon in the interior of the assembly.

U.S. Patent No. 5,219,355 discloses an intraluminal prosthesis for repairing aneurysms which utilizes a catheter having two inflatable balloons, one near each end of the prosthesis, for securing the prosthesis in place in the vessel.

While the retention systems appear to be effective in retaining the grafts in the vessel, over time, it is anticipated, and there have been some recent reports that the vessel wall where the graft connects thereto becomes weakened, and a subsequent aneurysm may occur at that position. As an additional factor, the penetration into the wall by the staples causes some fibrosis, and the tissue buildup at the location of the connection can cause some blood flow restriction which would increase the pressure on the vessel walls at the site of contact between the blood vessel and the graft. This condition may also increase the risk of a subsequent aneurysm.

The present invention is designed to operate in conjunction with a number of various retention systems for retaining a vascular graft in a vessel by attaching the graft to the interior wall of the vessel, without the risk. Each of these has certain deficiencies which are described below, which deficiencies are resolved by the present invention.

SUMMARY OF THE INVENTION

A method and apparatus are disclosed which overcome the disadvantages and limitations associated with the prior art devices, and which can be used in conjunction with the prior art system to ensure that the vessel retention system of a vascular graft functions without causing certain complications. More specifically, the complications, which may occur over time, relate to a weakening of the wall of the blood vessel at the attachment site of the graft to the vessel, causing an aneurysm at the new location, typically upstream, but possibly downstream from the original aneurysmic site. The secondary aneurysm is the result of the weakening of the wall of the blood vessel due to the use of staples to attach the graft to the vessel, and various other factors.

The present invention is an apparatus and method of alleviating this problem by applying to the blood vessel a band around its exterior surface, at the position where the attachment system of the graft attaches the graft to the vessel. The band can be in the form of a strap with an attachment means such as a Velcro®, or a clasp, or it can be heat sealed onto the vessel or sewn thereon. The band can be applied laparoscopically or using direct field of vision. Typically in the application of the graft it is inserted in the blood vessel downstream from the aneurysm and then advanced to the site of the aneurysm through the interior of the vessel, and then expanded into its full radial size and secured in place using the retention system designed for it, of the different systems known in the art. The position of the graft can be confirmed using x-ray or other imaging technique. Once the graft is in place and assembled and secured in place with its

retention system, the band can be applied to the exterior of the blood vessel. The length of the band can vary, but should be at least long enough to envelope the entire length of the blood vessel to which the graft is attached at the attachment site.

BRIEF DESCRIPTION OF THE DRAWINGS

The objects of the present invention will be described with respect to the following figures in which:

FIGURE 1 is an illustration of one type of prior art graft retention system.

FIGURE 2 is a partially cutaway view of a prior art graft with a retention system.

FIGURE 3 is a partial sectional view of an aneurytic blood vessel with a vascular graft disposed therein, and the band of the present invention disposed around the blood vessel at the site where the retention system engages the blood vessel.

FIGURE 4 is an enlarged view of a portion of the present invention disposed on a blood vessel with a retention system, taken through the section designated by the numeral 4 in Figure 3.

FIGURE 5 is a perspective view of one embodiment of the strap of the present invention.

FIGURE 6 is a perspective view of another embodiment of the present invention in a partially folded configuration.

FIGURE 7 is a perspective view of an alternative embodiment of the strap of the present invention.

FIGURE 8 is a perspective view of the another alternative embodiment of the strap of the present invention.

-7-

FIGURE 9 is a perspective view of another alternative embodiment of the strap of the present invention.

FIGURE 10 is a perspective view of a prior art vascular graft.

Figure 11 is a perspective view of the present invention being used to retain a vascular graft.

DETAILED DESCRIPTION OF THE INVENTION

An apparatus is described for securing on a blood vessel a vascular graft containing a retention system. A method of securing the vascular graft is also described. Renal arteries extend from the abdominal aorta and the arteries are divided into the common iliac artery at the lower most end. The aorta is a major blood vessel of the body and is characterized by generally healthy tissue. However, one section of the aorta is damaged, and this is where a large aneurysm has formed characterized by a bulge in the wall of the aorta. If the aneurysm is not repaired or otherwise treated in time it will eventually rupture causing a fatal hemorrhage within a short period of time. It will be understood by persons of skill in the art that while the present invention is described with reference to an aneurysm in the aorta, the present invention will be useful in the treatment of aneurysm in other vessels as well, the usefulness of the vascular graft technology in the repair of aneurysm being generally known in the art.

The present invention is an adjunct to a prosthetic graft for repairing the damaged blood vessel. The prosthetic graft is primarily made of generally biologically acceptable material, such as Dacron, Nylon, Gortex, and the like. The graft is an elongated tube of the material and a retention systems for retaining the graft within the blood vessel. The retention system is comprised of a cylindrical array of staples which have outward protruding barbs. The retention system is expandable and collapsible, which is presently necessary and consistent with the method of implantation in which the graft is installed in a blood vessel at a site remote from the aneurysm, and is

then pushed and guided up to the aneurytic site, and then installed in place in the blood vessel.

Figure 1 is an illustration of one prior art graft retention system in which the staples are collapsible and expandable. The graft retention system 10 comprises a plurality of staples or barbs 12 extending outward, and connected together in a v-shaped network with a spring hinge 14 interconnecting each staple. It will be appreciated by persons of skill in the art that there are a number of different graft retention systems, including a variety of different staple configurations and balloon retention systems, and the present invention will work with any of these systems. As shown in Figure 2, the graft retention system of Figure 1 is disposed within the vascular graft 16, shown in a partially cutaway view, with the retention system 10 being partially viewable above and below the edges 17 and 18 of the graft. The graft retention system 10 is retained in the graft by any suitable means.

Figure 3 illustrates the present invention which is a band disposed around the exterior of the blood vessel at the location where the retention system is connected to the blood vessel remote from the actual position of the aneurysm. More specifically, the graft 16 is disposed at the site of the aneurysm 20 in the aorta 22. Figure 3 is a partially cutaway sectional view of the invention disposed in place on the aorta 22 showing that at one end 24, the retention system 10a, shown partially in ghost lines, retains the graft 16 in the aorta 22, and the band 26 of the present invention, shown in sectional view, is disposed around the exterior of the aorta 22 at the location where the

-10-

retention system 10a joins the graft 16 to the interior of the aorta 22. As a result of the positioning of the band 26, the aorta is supported and the graft 16 is secured in position. At the other end 25 of the graft 16, a second band 30 is shown in full form with the underlying retention system and graft shown in ghost lines. As can be seen, the band is sufficiently wide to carefully overlie the site where the retention system connects to the aorta, but not so wide so as to restrict the natural motion of the blood vessel in operation. It will also be appreciated by persons of skill in the art that the band can be of any width which will accomplish the intended purpose of supporting the blood vessel at the site of the connection between the graft and the blood vessel.

Figure 4 shows an enlarged view of the present invention strap 26 installed on a blood vessel 22 with a retention system 10a holding the graft 16 to the interior wall of the vessel 22. It will be appreciated that although in the present invention, the barb 28 is disposed entirely through the wall of the vessel 22, the barb 28 does not have to extend all the way therethrough in order for the present invention to function properly. While not being bound to any particular theory, the present invention functions by supporting the blood vessel and preventing it from expanding beyond its natural amount of expansion. It works like a girdle to provide the required support.

As shown in Figure 5, one embodiment of the present invention is a strap that may be wrapped around a blood vessel to provide a snug fit, and then locked in place by any suitable means known in the art. Examples of suitable means are described in more detail below.

but generally may including sewing, adhesives, melting using a cauterizing instrument or the like, hook and loop type fasteners, other bands or fasteners, snaps, belt buckles, friction type buckling systems, or other systems known in the art.

As shown in Figure 6, one embodiment of the present invention is disclosed in which the strap 32 is generally a flat strap with mating hook and loop type fastening means (Velcro®) disposed on opposite sides of the strap so that they mate when the strap is folded into a circular configuration, and are used to lock the strap around a blood vessel. The hook and loop system, depicted by numerals 34a and 34b, are sufficiently long and disposed along a sufficient length of the strap 32 that the strap will have the desired length when closed around a blood vessel to provide the desired snug fit.

As shown in Figure 7, another embodiment of the present invention also utilizes a strap 40 with a hook and loop system, 42a and 42b disposed on the same side of the strap 40, and a buckle 44 through which end 46 of strap 40 is disposed, so that the strap 40 doubles back on itself and is locked in a closed circular configuration.

As shown in Figure 8, in another embodiment of the present invention is a strap 50, similar to the form shown in Figure 5, in which the ends 52 and 54 are sewn together with stitching 56.

As shown in Figure 9, in another embodiment of the present invention is a strap 60 having a plurality of detents or ridges 62 on one surface and a buckle 64, like a cable tie buckle, which is known in the art, which locks the strap in a circular configuration when the end

66 is passed through the buckle 64 and pulled tight. This arrangement is advantageous because there are devices which can tighten such a strap to a desired tension, and such tensioning devices are already in use in medical, and particularly, surgical, applications. One example of such a tensioning device for these straps is a Panduit GS2B (Tinley Park, Illinois).

As shown in Figures 10 and 11, the present invention can be used to secure an intraluminal vascular prosthesis or graft. A section of the aorta is shown with a dilated lumen as is known in the art. The graft 70, which is known in the art and can be obtained commercially from companies such as C.R. Bard, Inc., Vascular Systems Division, Billerica, Massachusetts. The graft can be attached to the section of the aorta by means of the present invention 72a and 72b which is disposed within the walls of the lumen.

While the method and apparatus have been described in terms of various embodiments, other embodiments may come to mind to those skilled in the art without departing from the spirit and scope of the present invention. The invention should, therefore, be measured in terms of the claims which follow.

CLAIMS**What I claim is:**

1. An aortic graft assembly comprising:
a generally liquid impervious body having a first and second end,
a graft retention system disposed at each of said first and second ends for retaining said graft in a blood vessel,
a support strap adapted to surround the exterior of a blood vessel, said support strap having a closure means for retaining said strap in a circular configuration when said strap is disposed around a blood vessel at a location adjacent to each of said graft retention systems.
2. The aortic graft assembly of claim 1 wherein said support strap comprises a closure means comprising a hook and loop fastener.
3. The aortic graft assembly of claim 1 wherein said support strap comprises a closure means comprising a loop to permit said support strap to double back on itself and a hook and loop type fastener on one side of said strap to secure said strap.
4. The aortic graft assembly of claim 1 wherein said support strap comprises a closure means comprising a suture.

5. The aortic graft assembly of claim 1 wherein said graft retention system comprises outwardly facing staples and said support strap is aligned with said staples.

6. The aortic graft assembly of claim 1 wherein said graft comprises a flexible, radially rigid tube, and said support strap couples said tube to two separated ends of a blood vessel.

7. In a vascular graft for resolving an aneurysm in a blood vessel of the type comprising a generally liquid impervious, tubular, collapsible and expandable body having a first and second end, and a graft retention system disposed at each of said first and second ends for retaining said graft in a blood vessel, in use, said graft retention system being collapsible and expandable, the improvement comprising a support strap adapted to surround the exterior of said blood vessel, said support strap having a closure means for retaining said strap in a circular configuration when said strap is disposed around a blood vessel at a location adjacent to each of said graft retention systems.

8. The support strap of claim 7, said support strap having a closure means comprising a hook and loop fastener.

9. The support strap of claim 7, said support strap having a closure means comprising a loop to permit said support strap to double back on itself and a hook and loop type fastener on one side of said support strap to secure said strap.

10. The support strap of claim 7, said support strap having a closure means comprising a suture.

11. A method of repairing an aneurytic blood vessel by inserting in said blood vessel at a location remote from the site of the aneurysm a vascular graft, positioning the graft at the site of the aneurysm, and securing said vascular graft to said blood vessel with a graft retention system, said graft retention system being secured to said blood vessel at positions on each side of said aneurysm, the improvement comprising securing around the exterior of said blood vessel at positions adjacent each of said graft retention systems, a strap.

12. The method of claim 11 wherein said strap is applied around said blood vessel at a predetermined tension.

13. The method of claim 12 wherein said strap is applied around said blood vessel at a predetermined tension by an adjustable tension gauge device.

14. The method of claim 12 wherein said strap is secured around said blood vessel by a strap retention means comprising a suture.

15. The method of claim 12 wherein said strap is secured around said blood vessel by a strap retention means comprising a hook and loop type fastener.

16. The method of claim 12 wherein said support strap comprises a closure means comprising a loop to permit said support strap to double back on itself and a hook and loop type fastener on one side of said strap to secure said strap.

17. The method of claim 12 wherein said support strap is closed by heating said support strap to heat weld it to itself.

1/3

FIG. 1




FIG. 3





FIG. 2

2/3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 9






FIG. 8

3/3



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US95/11350

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A61P 2/06

US CL : 623/001

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 623/001

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

NONE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US, A, 4,190,909 (ABLAZA) 04 March 1980, see columns 2 and 3.	1, 4, 6, 7, 10-12, 14 2, 3, 8, 9, 13, 15-17
Y	US, A, 5,084,065 (WELDON ET AL.) 28 January 1992, see column 6.	2, 3, 8, 9, 13, 15-17



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be part of particular relevance

E earlier document published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another claim or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X

documents of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z

document member of the same patent family

Date of the actual completion of the international search

26 OCTOBER 1995

Date of mailing of the international search report

05 DEC 1995

Name and mailing address of the ISA/US

Commissioner of Patents and Trademarks

Box PCT

Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

FOR

PAUL ZUTTARELLI

Telephone No. (703) 308 3055

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.